
Amphenol®



Amphenol® TMPC POWER MOUNT Flange Mounted Traction Motor Power Connector series featuring RADSOK® Contacts.

Amphenol Industrial Operations introduces the addition of our "NEW" TMPC Power Mount flange mounted connector series. The New TMPC Power Mount series is an addition to our time tested TMPC Single Pin power connector line. The TMPC Power Mount incorporates our existing TMPC connectors with RADSOK® contacts into our new thermoplastic molded receptacle flange.

Available in color codes per the NEC AC/DC Electrical requirements, the TMPC Power Mount series is designed to work with current IEEE Type P drilling cables (sizes range from 313 MCM through 777 MCM). The RADSOK® contacts allow for higher amperages and reduced insertion/removal forces when compared to similar products in the market.

Features & Benefits:

- RADSOK® contact provide increased amperages than competition
- · Contacts rated at 1500 amp for 777 MCM cables
- Contacts machined from high grade copper to offer longer life, more mating cycles
- Lower insertion/removal forces is a by-product of our RADSOK® contacts
- Molded flange base mounts directly to Stainless or Aluminum panels, thus eliminating the need for added secondary mounting fixtures
- Color coded mounting bases and cable side boots available to help prevent cross mating, while allowing easier electrical phase identification
- Connector series comes complete with molded Hypalon caps and insulation boots
- Patent Pending

PLUG ASSEMBLIES W/PIN CONTACTS

COLOR	313 MCM	444 MCM	535 MCM	646 MCM	777 MCM
Black	TMPC-SP3-BK	TMPC-SP4-BK	TMPC-SP5-BK	TMPC-SP6-BK	TMPC-SP7-BK
Blue	TMPC-SP3-BL	TMPC-SP4-BL	TMPC-SP5-BL	TMPC-SP6-BL	TMPC-SP7-BL
Brown	TMPC-SP3-BR	TMPC-SP4-BR	TMPC-SP5-BR	TMPC-SP6-BR	TMPC-SP7-BR
Green	TMPC-SP3-G	TMPC-SP4-G	TMPC-SP5-G	TMPC-SP6-G	TMPC-SP7-G
Gray	TMPC-SP3-GY	TMPC-SP4-GY	TMPC-SP5-GY	TMPC-SP6-GY	TMPC-SP7-GY
Orange	TMPC-SP3-OR	TMPC-SP4-OR	TMPC-SP5-OR	TMPC-SP6-OR	TMPC-SP7-OR
Purple	TMPC-SP3-P	TMPC-SP4-P	TMPC-SP5-P	TMPC-SP6-P	TMPC-SP7-P
Red	TMPC-SP3-R	TMPC-SP4-R	TMPC-SP5-R	TMPC-SP6-R	TMPC-SP7-R
White	TMPC-SP3-W	TMPC-SP4-W	TMPC-SP5-W	TMPC-SP6-W	TMPC-SP7-W
Yellow	TMPC-SP3-Y	TMPC-SP4-Y	TMPC-SP5-Y	TMPC-SP6-Y	TMPC-SP7-Y

RECEPTACLE KIT PART NUMBERS					
COLOR	FLANGE KIT W/CONTACT	FLANGE KIT LESS CONTACT	BOOT PART		
Black	TMPC-SR-BK	TMPC-SRLC-BK	TMPC-10-BK		
Blue	TMPC-SR-BL	TMPC-SRLC-BL	TMPC-10-BL		
Brown	TMPC-SR-BR	TMPC-SRLC-BR	TMPC-10-BR		
Green	TMPC-SR-G	TMPC-SRLC-G	TMPC-10-G		
Gray	TMPC-SR-GY	TMPC-SRLC-GY	TMPC-10-GY		
Orange	TMPC-SR-OR	TMPC-SRLC-OR	TMPC-10-OR		
Purple	TMPC-SR-P	TMPC-SRLC-P	TMPC-10-P		
Red	TMPC-SR-R	TMPC-SRLC-R	TMPC-10-R		
White	TMPC-SR-W	TMPC-SRLC-W	TMPC-10-W		
Yellow	TMPC-SR-Y	TMPC-SRLC-Y	TMPC-10-Y		

CONTACTS ONLY (FOR RETENTION RING ADD -RR)						
CABLE SIZE	BUSBAR CONTACT	PIN CONTACT				
313 MCM	TMPC-1	TMPC-40535-RL				
444 MCM	TMPC-1	TMPC-40535-RL				
535 MCM	TMPC-1	TMPC-40535-RL				
646 MCM	TMPC-1	TMPC-40777-RL				
777 MCM	TMPC-1	TMPC-40777-RL				

ACCESSORIES					
DESCRIPTION	PART NUMBER				
RECEPTACLE CAP	TMPC-SR-CAP				
BOOT CAP	TMPC-SP-CAP				
MOUNTING GASKET	TMPC-SR-G				
BOOT RING 313 MCM	SR1-313R				
BOOT RING 444 MCM	SR1-444R				
BOOT RING 535 MCM	SR1-535R				
BOOT RING 646 MCM	SR1-646R				
BOOT RING 777 MCM	SR1-777R				

Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors.

AMPHENOL is a registered trademark of Amphenol Corporation.

For further information on your individual application requirements, contact: Amphenol Corporation

North America: Amphenol Industrial Operations 180 N. Freeport Drive, Plant 4 Nogales, AZ 85621 Tel: (520) 285-5130 Fax: (520) 285-5134

Amphenol Industrial Operations Europe
Via Barbaiana 5
1-20020 Lainate (MI) Italy
Tel: +39 02 93254.204
Fax: +39 02 93254.444

Middle East:
Amphenol Middle East Enterprises FZE
Office C-37 PO Box 21107
Ajman Free Zone, UAE
Tel: +9716-7422494
Fax: +9716-7422941

Asia:
Amphenol Technology Shenzhen Ltd
Block 5 Fuan 2nd Industrial Park
Dayang Rd, Fuyong Baoan
Baoan, Shenzhen, China 518103
Tel; +86 755 2881 8389
Fax; +86 755 2991 8310
Fmail: ennuirv@amphenol-aio.com